



## SAFETY DATA SHEET NO.25 SATIN MATT BLACK PAINT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** NO.25 SATIN MATT BLACK PAINT  
**Product number** 25012B, 25012B\*OP10, 25012SP, 25012REN

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Automotive paint preparation

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Autoglym  
Works Road  
Letchworth  
Herts  
SG6 1LU  
UK  
sds@autoglym.com

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1462 489498 (24Hrs)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture


##### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** Vapours and spray/mists in high concentrations are narcotic.  
**Environmental** The product is not expected to be hazardous to the environment.  
**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up.  
The product is extremely flammable. Vapours may form explosive mixtures with air.

#### 2.2. Label elements

##### Pictogram



**Signal word** Danger

## NO.25 SATIN MATT BLACK PAINT

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P271 Use only outdoors or in a well-ventilated area. P261 Avoid breathing vapour/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	Acetone, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Butanone, N-Butyl Acetate, Solvent naphtha (petroleum), light arom., Hydrocarbons, C6, isoalkanes, <5% n-hexane

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>Petroleum Gases, Liquified</b>	<b>30-60%</b>
CAS number: 68476-85-7	EC number: 270-704-2
	REACH registration number: 01-2119485911-31-XXXX
<b>Classification</b>	
Flam. Gas 1 - H220	
<b>Acetone</b>	<b>10-30%</b>
CAS number: 67-64-1	EC number: 200-662-2
	REACH registration number: 01-2119471330-49-XXXX
<b>Classification</b>	
Flam. Liq. 2 - H225	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Eye Irrit. 2 - H319	F;R11 Xi;R36 R66 R67
STOT SE 3 - H336	

## NO.25 SATIN MATT BLACK PAINT

<b>N-Butyl Acetate</b>		<b>5-10%</b>
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 R66 R67	
<b>2-Methoxy-1-methylethyl Acetate</b>		<b>5-10%</b>
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-XXXX
<b>Classification</b> Flam. Liq. 3 - H226	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10	
<b>Butanone</b>		<b>5-10%</b>
CAS number: 78-93-3	EC number: 201-159-0	
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R66 R67	
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>		<b>5-10%</b>
CAS number: 64742-49-0	EC number: 921-024-6	REACH registration number: 01-2119475514-35-XXXX
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>Solvent naphtha (petroleum), light arom.</b>		<b>1-5%</b>
CAS number: 64742-95-6	EC number: 265-199-0	REACH registration number: 01-2119486773-24-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Muta. 1B - H340 Carc. 1B - H350 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

**NO.25 SATIN MATT BLACK PAINT**

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>	<b>1-5%</b>
CAS number: 64742-49-0	EC number: 931-254-9
	REACH registration number: 01-2119484651-34-XXXX
<b>Classification</b>	
Flam. Liq. 2 - H225	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

**4.2. Most important symptoms and effects, both acute and delayed**

<b>General information</b>	See Section 11 for additional information on health hazards.
----------------------------	--

**4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	Use foam, carbon dioxide or dry powder to extinguish.
-------------------------------------	---

**5.2. Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

**5.3. Advice for firefighters**

<b>Protective actions during firefighting</b>	Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
---	--

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
-----------------------------	---

**6.2. Environmental precautions**

## NO.25 SATIN MATT BLACK PAINT

**Environmental precautions**      Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up**      Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections**      For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions**              Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

**Advice on general occupational hygiene**      Wash promptly with soap and water if skin becomes contaminated.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions**              Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

**Specific end use(s)**              The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **Petroleum Gases, Liquefied**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

##### **Acetone**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **N-Butyl Acetate**

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

##### **2-Methoxy-1-methylethyl Acetate**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m<sup>3</sup>

Sk

##### **Butanone**

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### 8.2. Exposure controls

## NO.25 SATIN MATT BLACK PAINT

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
<b>Hand protection</b>	No specific hand protection recommended.
<b>Other skin and body protection</b>	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
<b>Respiratory protection</b>	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Solvent.
<b>Odour threshold</b>	No information available.
<b>pH</b>	No information available.
<b>Melting point</b>	No information available.
<b>Flash point</b>	-40°C Closed cup.
<b>Evaporation rate</b>	No information available.
<b>Evaporation factor</b>	No information available.
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 13.0 %
<b>Vapour pressure</b>	No information available.
<b>Vapour density</b>	No information available.
<b>Relative density</b>	0.702
<b>Partition coefficient</b>	No information available.
<b>Auto-ignition temperature</b>	333°C
<b>Decomposition Temperature</b>	No information available.
<b>Viscosity</b>	No information available.
<b>Oxidising properties</b>	No information available.

#### 9.2. Other information

<b>Other information</b>	None.
--------------------------	-------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	The product may not be stable under some conditions of storage or use.
------------------	--

#### 10.3. Possibility of hazardous reactions

## NO.25 SATIN MATT BLACK PAINT

**Possibility of hazardous reactions** Not known.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** None known.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None at ambient temperatures.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 1,100.0

**Inhalation** Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

**Skin contact** No significant hazard at normal ambient temperatures.

**Eye contact** Vapour or spray in the eyes may cause irritation and smarting.

**Acute and chronic health hazards** No known chronic or acute health risks.

**Route of exposure** Inhalation Skin and/or eye contact

## SECTION 12: Ecological Information

### 12.1. Toxicity

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Partition coefficient** No information available.

### 12.4. Mobility in soil

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations

## NO.25 SATIN MATT BLACK PAINT

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

#### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)



## NO.25 SATIN MATT BLACK PAINT

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Revision date</b>	23/04/2015
<b>Revision</b>	4
<b>SDS number</b>	20944
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects. H350 May cause cancer. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
<b>Signature</b>	Daniel Higgs