

POLISHFLEX, variable-speed polisher with a high torque

PE 14-2 150

Order number 373.680



Technical attributes

Max. polishing pad diameter	200 mm
Max. back-up pad diameter	150 mm
No load speed	380-2100 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Cable length	4,0 m
Size (W x L x H)	405 x 84 x 117 mm
Weight	2,3 kg

POLISHFLEX, variable-speed polisher with a high torque

- + Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Innovative combination of planetary and angular gears reduces noise to an absolute minimum
- + Continuous speed control trigger: for a gentle start (starting speed at setting 1 (380 rpm)) and a lock-on for continuous operation
- + Microprocessor electronics: stepless speed selection, tachogenerator-controlled constant speed, overload protection, re-start protection and temperature monitoring
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down
- + Spindle lock: It is ideally positioned to prevent operating error and does not interfere with the grip area.
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions

Standard equipment

1 handle	252.721
----------	---------