FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



Safety vacuum cleaner with manual filter cleaning system, 20 l, class L

VC 21 L MC

Order number 405.418



Technical attributes Power input P. max. 1000 watt Max. volume flow 3600 l/min Max. vacuum 21000 Pa Filter surface 3000 cm² Container volume 20 l Liquid capacity 11 l Power take off 100-2000 watt Cable length 5,0 m

430 x 380 x 506 mm

7,4 kg

Safety vacuum cleaner with manual filter cleaning system, 20 l, class L

+ Handy and compact vacuum cleaner, easy to use and easy to transport

+ The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result

+ By actuating manual filter cleaning, dust deposited in the filter element is removed by a targeted blast of air

+ Level monitor, no malfunctions when drawing in liquids thanks to installed float valve

+ With appliance socket and electronic automatic switch on/off

+ Equipped with large wheels and two swivel guide rollers

+ Suitable for increased stress commercially (according EN 60335-2-69). Ideal for cleaning work in offices, storage rooms, workshops and vehicles. Smaller electric power tools, e.g. palm sander, delta sander, random-orbit sander, jigsaws, are primarily used for extraction work. Tools which produce fairly low amounts of dust

+ Features a filter bag made of highly tear-proof fleece for optimum filling. The extracted dust can be disposed of without difficulty

+ Safety vacuum cleaner, approved for dust class L, suitable for all dust with OEL value >1 $\rm mg/m^3$

Standard equipment

Size (W x L x H)

Weight

1 suction hose 32 mm Ø x 3.5 m with elbow	385.484
1 filter element class L/M	385.085
3x 35 cm INOX suction pipe	445.207
1 combination floor nozzle, switchable	385.565
1 round brush	385.646
1 crevice nozzle	385.530
1 upholstery nozzle	385.549
1 filter bag	502.235
1 PP waste disposal bag	385.107
1 suction pipe holder	410.993
1 cable hook	410.705
1 adapter Ø 27-32 mm	385.506