FLEX-Elektrowerkzeuge GmbH Bahnhofstraße 15 71711 Steinheim Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com



## Roto random orbit polisher

## XFE 7-15 150



## Roto random orbit polisher

- + 15 mm orbit for high efficiency
- + Free-spinning drive for hologram-free finishing
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Powerful 710 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Counterweight for smoother operation
- + Cushioned special hook and loop pad for polishing.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions

## **Order number 418.080**

Technical attributes	
Max. polishing pad diameter	160 mm
Max. back-up pad diameter	150 mm
<b>Orbit</b>	15 mm
No load speed	1500-4500 rpm
Orbit rate, no load	3000-9000 opm
Power input	710 watt
Power output	420 watt
Cable length	4,0 m
Size (W x L x H)	370 x 40 x 140 mm
Weight	2,4 kg

Standard equipment	
1 special hook-and-loop backing pad, 125 Ø	487.953
1 special hook-and-loop backing pad, 150 Ø	487.988